USAARL Report No. 94-38



AD-A285 182

Direct Comparison of Two Statistical Methods for Determination of Evoked-Potential Thresholds

By

Ted L. Langford James H. Patterson, Jr.



Aircrew Protection Division

July 1994



Approved for public release; distribution unlimited.





United States Army Aeromedical Research Laboratory Fort Rucker, Alabama 36362-0577

Notice

Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

Animal use

In conducting the research described in this report, the investigators adhered to the <u>Guide for Laboratory Animal Facilities and Care</u>, as promulgated by the Committee on the Guide for Laboratory Animal Resources, National Academy of Sciences-National Research Council.

Disposition

Destroy this document when it is no longer needed. Do not return it to the originator.

Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

Reviewed:

KEVIN T. MASON

LTC, MC, MFS

Director, Aircrew Protection

ein I Mason

Division

ROGER W. WILEY, O.D., Ph.D.

Chairman, Scientific

Review Committee

Released for publication:

V DAVID H. KARNEY

Colonel, MC, SFS

Commanding

	Form Approved OMB No. 0704-0188											
1a. REPORT SEC Unclassifi		IFICATION		1b. RESTRICTIVE MARKINGS								
2a. SECURITY C		N AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT								
2b. DECLASSIFIC	CATION / DOW	NGRADING SCHEDU	LE	Approved for public release, distribution unlimited								
4. PERFORMING	ORGANIZAT	ION REPORT NUMBE	R(S)	5. MONITORING ORGANIZATION REPORT NUMBER(\$)								
USAARL Re	port No.	94-38										
	Aeromedi	ORGANIZATION cal Research	6b. OFFICE SYMBOL (If applicable) SGRD-UAS-AS	7a. NAME OF MONITORING ORGANIZATION U.S. Army Medical Research, Development, Acquisition and Logistics Command								
6c. ADDRESS (C	ity, State, an	d ZIP Code)	00.00	7b. ADDRESS (City, State, and ZIP Code)								
P.O. Box 6 Fort Rucke		6362-0577		Fort Detrick Frederick, MD 21702-5012								
8a. NAME OF F ORGANIZAT		NSORING	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER								
8c. ADDRESS (C	ity, State, and	ZIP Code)		10. SOURCE OF	FUNDING NUMBER	S						
				PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.					
				61102A	30161102BS1	5 ЈВ	282					
Direct com	11. TITLE (Include Security Classification) Direct comparison of two statistical methods for determination of evoked-potential thresholds 12. PERSONAL AUTHOR(\$) Ted L. Langford and James H. Patterson, Jr.											
13a. TYPE OF R	REPORT	13b. TIME CO FROM_	OVERED TO	14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT 1994 July 11								
16. SUPPLEMEN	ITARY NOTAT	TION										
17.	COSATI		18. SUBJECT TERMS (=	-						
FIELD 05	GROUP 01	SUB-GROUP	Evoked potent: chinchilla	ials, objective threshold determination,								
06	04											
19. ABSTRACT (Continue on reverse if necessary and identify by block number) Several statistical procedures have been proposed as objective methods for determining evoked-potential thresholds. Data have been presented to support each of the methods, but there have not been direct comparisons using the same data. The goal of the present study was to evaluate correlation and variance ratio statistics using common data. A secondary goal was to evaluate the utility of a derived potential for determining thresholds. Chronic, bipolar electrodes were stereotaxically implanted in the inferior colliculi of six chinchillas. Evoked potentials were obtained at 0.25, 0.5, 1.0, 2.0, 4.0 and 8.0 kHz using 12-ms tone bursts and 12-ms tone bursts superimposed on 120-ms pedestal tones which were of the same frequency as the bursts, but lower in amplitude by 15 dB. Alternate responses were averaged in blocks of 200 to 4000 depending on the size of the response. Correlations were calculated for the pairs of averages. A response was deemed present if DICENTIFY THE SCURITY CLASSIFICATION 21. ABSTRACT SECURITY CLASSIFICATION Unclassified Unclassified												
22a. NAME OF	RESPONSIBLE	INDIVIDUAL	FI. LI DIIC USERS	22b. TELEPHONE (Include Area Code) 22c. OFFICE SYMBOL								
Chief, Science Support Center 205-255-6907 SGRD-UAX-SI												

19. Abstract (continued).

the correlation coefficient reached the 0.05 level of significance in 4000 or fewer averages. Threshold we efined as the mean of the level at which the correlation was significant and a level 5 dB below that at which it was not. Variance ratios were calculated as described by Elberling and Don (1984) using the same data. Averaged tone burst and tone burst-plus pedestal data were differenced and the resulting waveforms subjected to the same statistical analyses described above. All analyses yielded thresholds which were essentially the same as those obtained using behavioral methods. When the difference between stimulus durations is taken into account, however, evoked-potential methods produced lower thresholds than behavioral methods.

							Ta	ab]	le	01	<u> </u>	201	nte	ent	ts.											
										•															P	age
List o	of fig	ures	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
Intro	duction	n.	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•		•	•	3
Method	ds .		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	4
Equip	ment a	nd p	roc	ed	ur	es	;	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	5
Result	ts and	dis	cus	ssi	on	l	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	7
Concl	usions		•	•	•		•	•	•	•	•	•	•	•	•	•	•		•		•	•		•	•	9
Refer	ences		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	10
Figur	e						I	Lis	st_	0	<u>f_</u> :	fic	gui	res	<u>\$</u>										F	age
1.	T	iora one- one- ombi atio	bur bur nec	rst rst	e : e	vc vc	oke oke fi	ed ed cor	t) t) n (hro	esi esi rro	no. no.	lds lds at:	s o	of rep	pı ore	ces es	ser ent	nt :	st	cuć		•	•	•	8
2.	ti C	ntio ith hres orre orre hres	der hol lat	riv lds tic	ed r n n	er ar ar	hi ore nd nd	ces ese va va	she ent ar:	olo to ia:	ds cor nce	mb: e :	To ind rat	oned tio	e-1 da 0 1	bui ata nei dei	cst a t the	t e fro ods vec	evo om s.	oke	èd			•	•	9

Acces	ion For
LIII	ORASI D
	Coenced []
By Distrik	z tion/
,	wellability Cons
Dist	Avail - 1) or Special
A-1	

			===
This page	intentionally	y • 	عادة ا

Introduction

The chinchilla currently is the animal of choice for use as a model to establish the effects of various parameters of noise and blast exposure on auditory structure and function.

The behavioral methods in use for measuring hearing in the animal model are based on conditioning techniques (Miller, 1970; Blakeslee, et al., 1978). These methods provide valid and reliable measures of auditory thresholds when properly used, but do have limitations. First, the data may be affected by differing animal motivation from session to session and by the training procedures, particularly when multiple experimenters contribute to a single data pool. Second, the large investment of time and effort for both the training and measurement phases of an experiment limits the rate at which animals can be processed and makes the loss of an animal from a project extremely costly to the overall effort. A rapid, objective method for measuring hearing in the animal model would eliminate these limitations of the behavioral procedures.

A rapid method of threshold assessment, based on the detection of electrical responses of the auditory system to sound stimuli, now is being used in some laboratories (Bancroft, et al., 1991). A chronic electrode is implanted in the auditory system, usually in the inferior colliculus, and time-locked responses evoked by brief, rapidly repeated tone bursts are recorded, then averaged to improve the signal-to-noise ratio. Several stimulus presentations are made per second and a response can be detected visually in the averaged waveform after several hundred presentations. The thresholds obtained in this manner compare well with those derived from behavioral methods when signals of the same duration are used for both measures (Henderson, et al., 1983). Visual detection of the response is not objective, however, so it is subject to problems such as criterion differences between experimenters and criterion shifts across time for individual experimenters.

Several objective methods of detecting averaged electrical responses have been proposed for use in human evoked-response audiometry. Two of the methods outlined below have shown the most promise in terms of objectivity and reliability:

A statistical method based on correlation has been used by Arnold (1985), Salvi, et al. (1987), and Weber and Fletcher (1980). If time-locked responses to stimuli are present, the correlation between two averaged samples of those responses will be greater than that of the background activity. The background noise at the recording site is assumed to be random in the absence of a stimulus, so averaged samples of the noise taken at different times will not be correlated with one another. To

determine objectively the presence of responses, samples of activity time-locked to the stimulus are taken, averaged, and the correlation calculated between the two sets of averages. If the obtained correlation is greater significantly than that of the background, or zero, a response is present.

A second statistical method is based on evaluation of the ratio of the variance of the background noise to that of the response evoked by the stimulus (Elberling and Don, 1984; Don, Elberling and Waring, 1984). The variance for the background noise is estimated by sampling a single point of the response waveform across individual stimulus presentations. The variance of the response is calculated across points of the averaged recorded waveform. The ratio of the two variances follows the F-distribution and can be used to determine the presence of a response with any desired probability of error.

The third method, originally based on the visual detection of a derived response of the cochlear potential (Pantev and Pantev, 1982; Pantev et al., 1985), has been adapted by Berlin and his coworkers (Berlin et al., 1991; Hood et al., 1991) for use in evoked response work involving the central auditory system. A tone burst, some 20 dB above threshold, repeatedly is presented together with a continuous tone of the same frequency, but at a level near the expected threshold. The tone burst then is presented without the continuous tone. The responses to each of the stimulus configurations are averaged separately, and then the two sets of averaged data are differenced. The result is the response to the continuous tone. Lower thresholds have been obtained with this method than with more conventional methods. In addition, as the continuous tone has a narrower bandwidth than the tone burst, the derived response is more frequency-specific than can be obtained with conventional methods.

Each of these methods appears to have merit when compared with conventional, visual methods of threshold estimation, but they never have been directly compared with one another. The present experiment was designed to compare the two objective statistical methods with one another using both conventional tone-burst data and derived data from the differencing method of Berlin and his coworkers. The results will be compared with thresholds obtained using behavioral methods.

<u>Methods</u>

Six 1-to-2-year old male chinchillas bred and raised in the U.S. Army Aeromedical Research Laboratory (USAARL) colony were used as subjects. The animals were anesthetized by intramuscular injection of a combination of Ketamine (40 mg/kg) and Xylazine (2-5 mg/kg). The anesthetized animals were prepared for aseptic

surgery by plucking the fur from the top of the head, scrubbing the plucked area, and swabbing it with Betadine. A lubricant was applied to the eyes to prevent drying. The animal then was placed in a stereotaxic instrument and draped. An incision was made near the midline, the skin retracted, and the exposed skull cleared of periosteum by scraping. The exposed portion of the skull then was coated with a solution of silver nitrate followed by a cyanoacrilate adhesive to provide a stable base for the cement used in fixing the electrode in place. The skull was marked according to previously determined stereotaxic coordinates and a dental burr was used to make a 2 mm opening. After cutting the dura, a concentric, bipolar electrode was lowered slowly into the left inferior colliculus while electrical activity evoked by a broadband click was monitored by an oscilloscope and an audio system. At the proper depth, as determined by the best response as well as by the stereotaxic coordinates, the electrode was cemented in place. The incision was closed and a topical antibiotic applied to the area.

Data collection was not initiated until a minimum of 2 weeks was allowed for recovery from the procedure.

The animal was restrained for the electrophysiological measurements in an apparatus designed for behavioral testing (Blakeslee, et al., 1978). The apparatus fixed the animal's head with respect to movement in the horizontal and coronal planes, but did not prevent pinna movement or rotation of the head about the interaural axis.

Equipment and procedures

Stimuli for the experiment were computer-generated and controlled. An inverse-FFT routine was used to generate the digital representations of the acoustic waveforms with experimenter-specified frequencies, durations, phases, and amplitude envelopes. The stimulus waveforms were calculated prior to the experimental sessions and stored in memory. experimental sessions, they were output via 16-bit D-to-A converters and filtered appropriately for the sampling rate. After conversion and low-pass filtering, the stimuli were amplified, then led to an electrically-shielded speaker located inside a double-walled, sound-insulated booth. The speaker was placed 1 meter in front of the animal. The sound field in the position occupied by the animal's head was calibrated at each frequency to be used prior to data collection. The calibration results were used by the software to set the stimulus levels desired for experimental conditions by means of a programmable attenuator.

The stimuli were 12 ms tone bursts at 250, 500, 1000, 2000, 4000, and 8000 Hz. They had rise and decay durations of 6 ms. Previous evoked-potential work using these stimuli (Langford, Mozo and Patterson, 1989) showed them to have acceptable signalto-noise ratios and bandwidths. The tone bursts were alternated with tone bursts temporally centered on a 120 ms tone of the same frequency, but at a level 15 dB below that of the burst. the time relation between the burst and the tone was fixed, the relative phases of the two differed at each frequency. frequency, the levels were varied in 5 dB steps over a 25 dB range encompassing the anticipated threshold. The number of repetitions was varied depending on the response magnitude obtained from each animal. In general, 200 to 400 repetitions for each level at each of four frequencies were run in each session. Each measurement session lasted approximately 45 minutes.

The experiment was designed so that the same data could be used to evaluate both of the statistical threshold determination methods under study. Data were collected beginning 3 ms after the onset of each tone burst for a period of 25.6 ms and for a like period of time beginning 51.2 ms after cessation of stimulation. This yielded background activity interleaved with responses to the tone bursts and with the tone bursts plus the long-duration tones. Each of the 25.6 ms data intervals contained 128 points. Data for each of the intervals were stored separately for off-line analysis.

The data for each stimulus condition were averaged later in blocks of 200 to 4000 repetitions. Each data epoch consisted of 128 points; however, adjacent points are not independent. The partial correlation between points has the effect of inflating the degrees of freedom used in the statistical tests. Since the lack of independence between points is a function of the frequency bandwidth used in the recording, autocorrelations were calculated for random noise samples generated with the same sampling rate and bandwidth used in data collection. The correlations approached zero when every fourth point was used in the calculations. Therefore, every fourth point was used in the computations of the correlations and variance ratios during data analysis.

Pairs of poststimulus waveforms, the results of averaging odd and even numbered responses to the stimulus presentations, were correlated (Pearson's r) with one another for each stimulus condition. The variance ratio for the entire set of data used in the correlation computations was calculated as F = VAR(S)/VAR(N). VAR(S) is the variance of the averaged postsignal data taken during the temporal interval presumably containing the response. VAR(N) is the background noise variance calculated for a single point across all responses. This method of estimating the noise

variance has been shown to be an accurate measure of the variance of the true background noise (Elberling and Don, 1984). A response was deemed to be present if the 0.05 level of statistical significance was reached in 4000 or fewer trials. Threshold was defined as the mean of the lowest level at which a response was present and the level 5 dB below it at which no response was present.

Results and discussion

Tone-burst condition

With the exception of one frequency in one animal, there was perfect agreement between the thresholds obtained by the correlation and variance ratio methods for the traditional tone burst data. Since the two thresholds in that one case differed by only 5 dB, they were averaged and the audiograms produced by the two methods were considered the same. The tone burst thresholds are compared with a database of 118 behavioral thresholds obtained from the chinchilla by Patterson, et al. (1991) in Figure 1. The greatest differences occur at 0.5 and 8 kHz, where the separation between the two is only 3.8 dB.

The durations of the stimuli used in obtaining the two sets of thresholds were not the same, however. The evoked-potential data were obtained using stimuli with an effective duration of 4 ms (Dallos and Olsen, 1964), while the behavioral data are based on stimuli with durations exceeding the upper limit for temporal integration in the chinchilla. Henderson (1969), as well as others (Wall and Ferraro, 1981; Davis and Ferraro, 1983) have shown the chinchilla integrates the energy of an auditory stimulus in the same manner as human subjects, at least for durations up to 100 ms. This would place the 4 ms threshold stimuli used in the present study some 14 dB below those used for obtaining the behavioral thresholds. Thus, the sensitivity of either of the objective statistical methods, when applied to conventional evoked potential data, is greater considerably than that of behavioral methods.

A study by Arnold (1985), who used supra-threshold click-evoked data obtained from human subjects, also compared the correlation and variance ratio methods with a subjective, visual method for determining the presence of a response. At 10 dB above behavioral threshold, the lowest level used in that study, the correlation method was slightly more sensitive than the visual method and the variance ratio was the least sensitive. Her method for estimating the variance of the background activity was different from that used in the present study, however. In addition, two replications of 2000 averaged repetitions of stimulus-evoked activity interleaved with two runs of 2000




Figure 1. Behavioral thresholds compared with conventional toneburst evoked thresholds of present study. Tone-burst evoked thresholds represent combined data from correlation and variance ratio methods.

averaged repetitions of background activity were used in those calculations, so that changes in the signal-to-noise ratio between samples could not be ruled out. Finally, no frequency-threshold values were obtained. Therefore, the results of that study cannot be compared directly with those of the present study.

Derived condition

The thresholds obtained from derived data using the two statistical methods did not show the high degree of correspondence found for the conventional tone-burst data. Differences of 5 dB between the correlation and variance ratio methods for at least one frequency in each of four animals were found. of these discrepancies, the thresholds for the two methods were treated separately. The two sets of thresholds are compared with the one obtained from the conventional tone burst method in Although others (Hood, et al., 1991) have reported Figure 2. lower thresholds for the chinchilla at the higher frequencies using the derived evoked-potential method, no such advantage was found in the present study. The thresholds based on the derived waveforms are parallel to and slightly higher than those obtained with the conventional method.




Figure 2. Conventional tone-burst evoked thresholds compared with derived thresholds. Tone-burst evoked thresholds represent combined data from correlation and variance ratio methods. Correlation and variance-ratio derived thresholds are plotted separately.

Several procedural differences between the two studies may explain the differences in the results. First, the thresholds reported by Hood, et al. (1991) were based on subjective, visual inspection of the data. Second, their evoked potentials were recorded from surface electrodes and may represent activity from different brain regions than those of the present study. Third, their continuous tones and tone bursts were not phase-locked as were those in the present study.

Conclusions

The objectively determined audiograms based on evokedpotential methods are parallel to those based on behavioral methods.

When the difference in stimulus duration between the evokedpotential and behavioral methods is taken into account, the evoked-potential method proves to be the more sensitive.

The derived-potential method, as implemented in the present study, is less sensitive than the conventional evoked-potential method.

References

- Arnold, S. A. 1985. Objective versus visual detection of the auditory brain stem response. <u>Ear and hearing</u>. 6:144-150.
- Bancroft, B. R., Boettcher, F. A., Salvi, R. J., and Wu, J. 1991. Effects of noise and salicylate on auditory evoked-response thresholds in the chinchilla. <u>Hearing research</u>. 54: 20-28.
- Berlin, C. I., Hood, L. J., Barlow, E. K., Morehouse, C. R., and Smith, E. G. 1991. Derived guinea pig compound VIIIth nerve action potentials to continuous pure tones. <u>Hearing research</u>. 52:271-280.
- Blakeslee, E. A., Hynson, K., Hamernik, R. P., and Henderson, D. 1978. Asymptotic threshold shift in chinchillas exposed to impulse noise. The journal of the acoustical society of America. 63:876-882.
- Dallos, P. J., and Olsen, W. O. 1964. Integration of energy at threshold with gradual rise-fall tone pips. <u>The journal of the acoustical society of America</u>. 36:743-751.
- Davis, R. I., and Ferraro, J. A. 1983. Temporal summation in normally and abnormally hearing chinchillas. The journal of auditory research. 23:281-292.
- Don, M., Elberling, C., and Waring, M. 1984. Objective detection of averaged auditory brainstem responses.

 <u>Scandinavian audiology</u>. 13:219-228.
- Elberling, C., and Don, M. 1984. Quality estimation of averaged auditory brainstem responses. <u>Scandinavian audiology</u>. 13:187-197.
- Henderson, D. 1969. Temporal summation of acoustic signals by the chinchilla. The journal of the acoustical society of America. 46:474-475.
- Hendersor). H., Hamernik, R. P., Salvi, R. J., and Ahroon, W. A. 1983. Comparison of auditory-evoked potentials and behavioral thresholds in the normal and noise-exposed chinchilla. Audiology. 22:172-180.
- Henderson, D., Onishi, S., Eldridge, D., and Davis, H. 1969. A comparison of chinchilla auditory evoked response and behavioral response thresholds. <u>Perception and psychophysics</u>. 5:41-45.

- Hood, L. J., Berlin, C. I., Heffner, R. S., Morehouse, C. R., Smith, E., and Barlow, E. K. 1991. Objective auditory threshold estimation using sine-wave derived responses. Hearing research. 55: 109-116.
- Langford, T. L., Mozo, B. T., and Patterson, J. H., Jr. 1989.

 <u>Evaluation of two objective measures of effective auditory stimulus level</u>. Fort Rucker, AL: U. S. Army Aeromedical Research Laboratory, USAARL Report No. 89-18.
- Miller, J. D. 1970. Audibility curve of the chinchilla. The journal of the acoustical society of America. 48:513-523.
- Pantev, C., Lagidze, S., Pantev, M., and Kevanishvili, Z. 1985. Frequency-specific contributions to the auditory brain stem response derived by means of pure-tone masking. <u>Audiology.24:275-287.</u>
- Pantev, C. and Pantev, M. 1982. Derived brain stem responses by means of pure-tone masking. <u>Scandinavian audiology</u>. 11: 15-22.
- Patterson, J. H., Jr., Carrier, M., Jr., Bordwell, K., Lomba Gautier, I. M., Hamernik, R. P., Ahroon, W. A., Turrentine, G., and Hargett, C. E., Jr. 1991. The hazard of exposure to impulse noise as a function of frequency. Fort Rucker, AL: U. S. Army Aeromedical Research Laboratory. USAARL Report No. 91-18. Volume 1.
- Salvi, R. J., Ahroon, W., Saunders, S. S., and Arnold, S. A. 1987. Evoked potentials: Computer-automated thresholdtracking procedure using an objective detection criterion. <u>Ear and hearing</u>. 8:151-156.
- Wall, L. G., and Ferraro, J. A. 1981. Temporal integration in the chinchilla. The journal of auditory research. 21:29-37.
- Weber, B. A. and Fletcher, G. L. 1980. A computerized scoring procedure for auditory brainstem response audiometry. <u>Ear and hearing</u>. 1:233-236.

Initial distribution

Commander, U.S. Army Natick Research,
Development and Engineering Center
ATTN: SATNC-MIL (Documents
Librarian)
Natick, MA 01760-5040

Library
Naval Submarine Medical Research Lab
Box 900, Naval Sub Base
Groton, CT 06349-5900

Chairman
National Transportation Safety Board
800 Independence Avenue, S.W.
Washington, DC 20594

Executive Director, U.S. Army Human Research and Engineering Directorate ATTN: Technical Library Aberdeen Proving Ground, MD 21005

Commander
10th Medical Laboratory
ATTN: Audiologist
APO New York 09180

Commander
Man-Machine Integration System
Code 602
Naval Air Development Center
Warminster, PA 18974

Naval Air Development Center Technical Information Division Technical Support Detachment Warminster, PA 18974 Commander
Naval Air Development Center
ATTN: Code 602-B
Warminster, PA 18974

Commanding Officer, Naval Medical Research and Development Command National Naval Medical Center Bethesda, MD 20814-5044 Commanding Officer Armstrong Laboratory Wright-Patterson Air Force Base, OH 45433-6573

Deputy Director, Defense Research and Engineering ATTN: Military Assistant for Medical and Life Sciences Washington, DC 20301-3080

Director Army Audiology and Speech Center Walter Reed Army Medical Center Washington, DC 20307-5001

Commander, U.S. Army Research Institute of Environmental Medicine Natick, MA 01760 Commander/Director
U.S. Army Combat Surveillance
and Target Acquisition Lab
ATTN: SFAE-IEW-JS
Fort Monmouth, NJ 07703-5305

Director
Federal Aviation Administration
FAA Technical Center
Atlantic City, NJ 08405

Commander, U.S. Army Test and Evaluation Command Directorate for Test and Evaluation ATTN: AMSTE-TA-M (Human Factors Group) Aberdeen Proving Ground, MD 21005-5055

Naval Air Systems Command Technical Air Library 950D Room 278, Jefferson Plaza II Department of the Navy Washington, DC 20361

Director
U.S. Army Ballistic
Research Laboratory
ATTN: DRXBR-OD-ST Tech Reports
Aberdeen Proving Ground, MD 21005

Commander
U.S. Army Medical Research
Institute of Chemical Defense
ATTN: SGRD-UV-AO
Aberdeen Proving Ground,
MD 21010-5425

Commander
USAMRDALC
ATTN: SGRD-RMS
Fort Detrick, Frederick, MD 21702-5012

Director Walter Reed Army Institute of Research Washington, DC 20307-5100 HQ DA (DASG-PSP-O) 5109 Leesburg Pike Falls Church, VA 22041-3258

Harry Diamond Laboratories ATTN: Technical Information Branch 2800 Powder Mill Road Adelphi, MD 20783-1197

U.S. Army Materiel Systems
Analysis Agency
ATTN: AMXSY-PA (Reports Pring)
Aberdeen Proving Ground
MD 21005-5071

U.S. Army Ordnance Center and School Library Simpson Hall, Building 3071 Aberdeen Proving Ground, MD 21005

U.S. Army Environmental
Hygiene Agency
ATTN: HSHB-MO-A
Aberdeen Proving Ground, MD 21010

Technical Library Chemical Research and Development Center Aberdeen Proving Ground, MD 21010-5423

Commander
U.S. Army Medical Research
Institute of Infectious Disease
ATTN: SGRD-UIZ-C
Fort Detrick, Frederick, MD 21702

Director, Biological Sciences Division Office of Naval Research 600 North Quincy Street Arlington, VA 22217 Commandant

U.S. Army Aviation
Logistics School ATTN: ATSQ-TDN

Fort Eustis, VA 23604

Headquarters (ATMD)
U.S. Army Training
and Doctrine Command
ATTN: ATBO-M
Fort Monroe, VA 23651

IAF Liaison Officer for Safety USAF Safety Agency/SEFF 9750 Avenue G, SE Kirtland Air Force Base NM 87117-5671

Naval Aerospace Medical Institute Library Building 1953, Code 03L Pensacola, FL 32508-5600

Command Surgeon HQ USCENTCOM (CCSG) U.S. Central Command MacDill Air Force Base, FL 33608

Director
Directorate of Combat Developments
ATTN: ATZQ-CD
Building 515
Fort Rucker, AL 36362

U.S. Air Force Institute of Technology (AFIT/LDEE) Building 640, Area B Wright-Patterson Air Force Base, OH 45433

Henry L. Taylor Director, Institute of Aviation University of Illinois-Willard Airport Savoy, IL 61874 Chief, National Guard Bureau ATTN: NGB-ARS Arlington Hall Station 111 South George Mason Drive Arlington, VA 22204-1382

Commander

U.S. Army Aviation and Troop Command ATTN: AMSAT-R-ES 4300 Goodfellow Bouvelard St. Louis, MO 63120-1798

U.S. Army Aviation and Troop Command Library and Information Center Branch ATTN: AMSAV-DIL4300 Goodfellow BoulevardSt. Louis, MO 63120

Federal Aviation Administration Civil Aeromedical Institute Library AAM-400A P.O. Box 25082 Oklahoma City, OK 73125

Commander
U.S. Army Medical Department
and School
ATTN: Library
Fort Sam Houston, TX 78234

Commander
U.S. Army Institute of Surgical Research
ATTN: SGRD-USM
Fort Sam Houston, TX 78234-6200

AAMRL/HEX Wright-Patterson Air Force Base, OH 45433

Air Unoiversity Library (AUL/LSE) Maxwell Air Force Base, AL 36112 Product Manager Aviation Life Support Equipment ATTN: SFAE-AV-LSE 4300 Goodfellow Boulevard St. Louis, MO 63120-1798

Commander and Director
USAE Waterways Experiment Station
ATTN: CEWES-IM-MI-R,
CD Department
3909 Halls Ferry Road
Vicksburg, MS 39180-6199

Commanding Officer Naval Biodynamics Laboratory P.O. Box 24907 New Orleans, LA 70189-0407

Assistant Commandant
U.S. Army Field Artillery School
ATTN: Morris Swott Technical Library
Fort Sill, OK 73503-0312

Mr. Peter Seib Human Engineering Crew Station Box 266 Westland Helicopters Limited Yeovil, Somerset BA20 2YB UK

U.S. Army Dugway Proving Ground Technical Library, Building 5330 Dugway, UT 84022

U.S. Army Yuma Proving Ground Technical Library Yuma, AZ 85364

AFFTC Technical Library 6510 TW/TSTL Edwards Air Force Base, CA 93523-5000 Commander Code 3431 Naval Weapons Center China Lake, CA 93555

Aeromechanics Laboratory
U.S. Army Research and Technical Labs
Ames Research Center, M/S 215-1
Moffett Field, CA 94035

Sixth U.S. Army ATTN: SMA Presidio of San Francisco, CA 94129

Commander
U.S. Army Aeromedical Center
Fort Rucker, AL 36362

Strughold Aeromedical Library
Document Service Section
2511 Kennedy Circle
Brooks Air Force Base, TX 78235-5122

Dr. Diane Damos
Department of Human Factors
ISSM, USC
Los Angeles, CA 90089-0021

U.S. Army White Sands
Missile Range
ATTN: STEWS-IM-ST
White Sands Missile Range, NM 88002

U.S. Army Aviation Engineering Flight ActivityATTN: SAVTE-M (Tech Lib) Stop 217Edwards Air Force Base, CA 93523-5000

Ms. Sandra G. Hart Ames Research Center MS 262-3 Moffett Field, CA 94035 Commander
USAMRDALC
ATTN: SGRD-UMZ
Fort Detrick, Frederick, MD 21702-5009

Commander
U.S. Army Health Services Command
ATTN: HSOP-SO
Fort Sam Houston, TX 78234-6000

U. S. Army Research Institute Aviation R&D Activity ATTN: PERI-IR Fort Rucker, AL 36362

Commander U.S. Army Safety Center Fort Rucker, AL 36362

U.S. Army Aircraft Development
Test Activity
ATTN: STEBG-MP-P
Cairns Army Air Field
Fort Rucker, AL 36362

Commander
USAMRDALC
ATTN: SGRD-PLC (COL R. Gifford)
Fort Detrick, Frederick, MD 21702

TRADOC Aviation LO Unit 21551, Box A-209-A APO AE 09777

Netherlands Army Liaison Office Building 602 Fort Rucker, AL 36362

British Army Liaison Office Building 602 Fort Rucker, AL 36362 Italian Army Liaison Office Building 602 Fort Rucker, AL 36362

Directorate of Training Development Building 502 Fort Rucker, AL 36362

Chief USAHEL/USAAVNC Field Office P. O. Box 716 Fort Rucker, AL 36362-5349

Commander, U.S. Army Aviation Center and Fort Rucker ATTN: ATZQ-CG Fort Rucker, AL 36362

Chief
Test & Evaluation Coordinating Board
Cairns Army Air Field
Fort Rucker, AL 36362

Canadian Army Liaison Office Building 602 Fort Rucker, AL 36362

German Army Liaison Office Building 602 Fort Rucker, AL 36362

French Army Liaison Office USAAVNC (Building 602) Fort Rucker, AL 36362-5021

Australian Army Liaison Office Building 602 Fort Rucker, AL 36362

Dr. Garrison Rapmund 6 Burning Tree Court Bethesda, MD 20817 Commandant, Royal Air Force Institute of Aviation Medicine Farnborough, Hampshire GU14 6SZ UK

Defense Technical Information Cameron Station, Building 5 Alexandra, VA 22304-6145

Commander, U.S. Army Foreign Science and Technology Center AIFRTA (Davis) 220 7th Street, NE Charlottesville, VA 22901-5396

Commander Applied Technology Laboratory USARTL-ATCOM ATTN: Library, Building 401 Fort Eustis, VA 23604

Commander, U.S. Air Force
Development Test Center
101 West D Avenue, Suite 117
Eglin Air Force Base, FL 32542-5495

Aviation Medicine Clinic TMC #22, SAAF Fort Bragg, NC 28305

Dr. H. Dix Christensen
Bio-Medical Science Building, Room 753
Post Office Box 26901
Oklahoma City, OK 73190

Commander, U.S. Army Missile
Command
Redstone Scientific Information Center
ATTN: AMSMI-RD-CS-R
/ILL Documents
Redstone Arsenal, AL 35898

Director Army Personnel Research Establishment Farnborough, Hants GU14 6SZ UK

U.S. Army Research and Technology Laboratories (AVSCOM) Propulsion Laboratory MS 302-2 NASA Lewis Research Center Cleveland, OH 44135

Commander
USAMRDALC
ATTN: SGRD-ZC (COL John F. Glenn)
Fort Detrick, Frederick, MD 21702-5012

Dr. Eugene S. Channing 166 Baughman's Lane Frederick, MD 21702-4083

U.S. Army Medical Department and School USAMRDALC Liaison ATTN: HSMC-FR Fort Sam Houston, TX 78234

Dr. A. Kornfield 895 Head Street San Francisco, CA 94132-2813

NVESD AMSEL-RD-NV-ASID-PST (Attn: Trang Bui) 10221 Burbeck Road Fort Belvior, VA 22060-5806

CA Av Med HQ DAAC Middle Wallop Stockbridge, Hants S020 8DY UK Dr. Christine Schlichting Behavioral Sciences Department Box 900, NAVUBASE NLON Groton, CT 06349-5900

Commander, HQ AAC/SGPA Aerospace Medicine Branch 162 Dodd Boulevard, Suite 100 Langley Air Force Base, VA 23665-1995

Commander Aviation Applied Technology Directorate ATTN: AMSAT-R-TV Fort Eustis, VA 23604-5577

COL Yehezkel G. Caine, MD Surgeon General, Israel Air Force Aeromedical Center Library P. O. Box 02166 I.D.F. Israel Director
Aviation Research, Development
and Engineering Center
ATTN: AMSAT-R-Z
4300 Goodfellow Boulevard
St. Louis, MO 63120-1798

Commander
USAMRDALC
ATTN: SGRD-ZB (COL C. Fred Tyner)
Fort Detrick, Frederick, MD 21702-5012

Commandant
U.S. Army Command and General Staff
College
ATTN: ATZL-SWS-L
Fort Levenworth, KS 66027-6900